



GYPSUM ASSOCIATION

SPECIFICATIONS

**APPLICATION AND FINISHING
OF GYPSUM PANEL PRODUCTS**

GA-216-2007

This document may be revised or withdrawn from circulation at any time. The status of the document should be verified by the user prior to following any recommendations contained herein. To verify that you have the most current edition of the document, access the Gypsum Association website at: www.gypsum.org.

TABLE OF CONTENTS

SECTION	PAGE
1. Scope and General Provisions	1
2. Definitions and Descriptions of Terms and Types of Materials for the Purposes of this Specification	1
3. Delivery, Identification, Handling, and Storage	2
4. Application of Gypsum Panel Products - General Provisions	3
5. Application of Single-Layer Gypsum Panel Products to Wood Framing Members	8
6. Application of Multi-Layer Gypsum Panel Products to Wood Framing Members	9
7. Adhesive Application to Wood Framing Members	9
8. Gypsum Panel Product Application over Steel Framing and Furring	10
9. Semi-Solid Gypsum Panel Products Partitions	11
10. Solid Gypsum Panel Products Partitions	11
11. Adhesive Application of Gypsum Panel Products to Interior Masonry, Concrete, or Brick Walls	11
12. Application of Gypsum Panel Products over Existing Interior Walls and Ceilings	12
13. Gypsum Panel Product Application over Rigid Plastic Foam Insulation	13
14. Application of Rigid Predecorated Combustible Panels (Paneling) to Gypsum Substrate	13
15. Application of Gypsum Panel Products to Receive Adhesively Applied Ceramic or Plastic Wall Tile or Plastic Finished Wall Panels	13
16. Outside Corners, Arches, and Curves	15
17. Exterior Applications of Exterior Gypsum Soffit Board, or Gypsum Panel Products	15
18. Electric Radiant Heating Systems for Gypsum Panel Product Ceilings	16
19. Finishing Gypsum Panel Products	16
Appendices	17
A.1 Application of Ceramic or Plastic Wall Tile or Plastic Finished Wall Panels over Gypsum Panel Products	17
A.2 Application of Water-Based Texture Finishes on Gypsum Panel Product Ceilings	18
A.3 Precautions to Minimize Potential of Sagging	18
A.4 Decoration of Gypsum Panel Products	18

Characteristics, properties, or performance of materials or systems herein described are based on data obtained under controlled test conditions and are for defined architectural or engineering end users. The Gypsum Association and its member companies make no warranties or other representations as to their characteristics, properties, or performance under any variation from such conditions or in uses in actual construction.

LIST OF TABLES AND FIGURES

TABLES	PAGE
1 Maximum Framing Spacing For Single-Layer Gypsum Panel Product	3
2 Maximum Weight of Overlaid Unsupported Insulation	4
3 Fastener Lengths For Gypsum Panel Product Application to Wood Framing	5
4 Multi-Layer Application Without Adhesive Between Layers	7
5 Multi-Layer Application With Adhesive Between Layers	7
6 Base Layer Fastener Spacing for Multi-Layer Gypsum Panel Product Application	7
7 Fastener Spacing with Adhesive or Mastic Application and Supplemental Fastening	9
8 Bending Radii	15
9 Thermal Performance Values of Gypsum Board	16

FIGURES	PAGE
1 Corner bead, trim, and casings	3
2 Typical control joint	5
3 Vertical section, ceiling framing oriented perpendicular to wall	6
4 Vertical section, ceiling framing oriented parallel to wall	6
5 Horizontal section through interior vertical angle	6
6 Single nailing	8
7 Double nailing	8
8 Adhesive application patterns	9
9 Direction of gypsum panel product application to steel framing	10
10 Shimmed plaster wall	12
11 Gypsum panel product substrate under rigid predecorated combustible paneling	13
12 Typical details - tub installation	14
13 Typical details - shower pan installation	14
14 Typical details - tub installation in fire-rated or sound-rated system	14
15 Typical soffit details	16
16 Tile in bath and shower should be brought up to the levels shown.	17