# ICC A117.1-2017

# Standard for Accessible and Usable Buildings and Facilities

American National Standard

International Code Council 500 New Jersey Avenue, NW, 6<sup>th</sup> Floor Washington, D.C. 20001

Approved March 28, 2017

American National Standards Institute 1899 L Street, NW, 11<sup>th</sup> Floor Washington, D.C. 20036



## Standard for Accessible and Usable Buildings and Facilities (ICC A117.1-2017)

First Printing: May 2017

ISBN: 978-1-60983-758-7

# COPYRIGHT ® 2017 By INTERNATIONAL CODE COUNCIL, INC.

ALL RIGHTS RESERVED. This 2017 ICC Standard for Accessible and Usable Buildings and Facilities (ICC A117.1-2017) is a copyrighted work owned by the International Code Council, Inc. Without advance written permission from the copyright owner, no part of this book may be reproduced, distributed, or transmitted in any form or by any means, including, without limitation, electronic, optical or mechanical means (by way of example, and not limitation, photocopying, or recording by or in an information storage retrieval system). For information on permission to copy material exceeding fair use, please contact: Publications, 4051 W. Flossmoor Road, Country Club Hills, IL 60478-5795. Phone 1-888-ICCSAFE (422-7233)

Trademarks: "ICC," the International Code Council logo and "Standard for Accessible and Usable Buildings and Facilities (ICC A117.1-2017)" are trademarks of the International Code Council, Inc.

### AMERICAN NATIONAL STANDARD

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgement of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he or she has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

**CAUTION NOTICE:** This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

### **FOREWORD**

(The information contained in this foreword is not part of this American National Standard (ANS) and has not been processed in accordance with ANSI's requirements for an ANS. As such, this foreword may contain material that has not been subjected to public review or a consensus process. In addition, it does not contain requirements necessary for conformance to the standard.)

### **Development**

The 1961 edition of ANSI Standard A117.1 presented the first criteria for accessibility to be approved as an American National Standard and was the result of research conducted by the University of Illinois under a grant from the Easter Seal Research Foundation. The National Easter Seal Society and the President's Committee on Employment of People with Disabilities became members of the Secretariat, and the 1961 edition was reaffirmed in 1971.

In 1974, the U.S. Department of Housing and Urban Development joined the Secretariat and sponsored needed research, which resulted in the 1980 edition. After further revision that included a special effort to remove application criteria (scoping requirements), the 1986 edition was published. When requested in 1987, the Council of American Building Officials (CABO) assumed the Secretariat. Central to the intent of the change in the Secretariat was the development of a standard that, when adopted as part of a building code, the standard would be compatible with the building code and its enforcement. The 1998 edition largely achieved that goal. The 2017 edition of the standard is the latest example of the A117.1 committee's effort to continue developing a standard that is compatible with the building code.

In 1998, CABO became the International Code Council (ICC). The International Code Council (ICC) became the secretariat in 1998 when CABO became ICC. The 2017 edition marks the 30th anniversary of the ICC Secretariat of the standard.

#### 2017 Edition

New to the 2017 edition are enhanced dimensions for clear floor spaces and turning spaces. These increases were in response to technical data regarding the space needed by persons using scooters and some types of motorized wheelchairs. These enhanced provisions only apply to new buildings and facilities. Where existing buildings and facilities are remodeled, the historic dimensions will still apply.

Other changes include exterior routes, curb cuts, blended transitions, clarity for detectable warnings, passenger drop offs and parking requirements coordinated with the Public Rights of Way Guidelines, providing an accessible design standard for electrical vehicle charging stations and enhanced safety for accessible routes crossing parking lots. Also introduced are acoustic standards for classrooms, features allowing for better communication for persons using sign language, provisions addressing the recharging of wheelchairs in assembly venues and hotels, access to





gaming machines and tables, and provisions for water bottle filling stations.

The new standard continues to provide coordination between the accessible provisions of this standard and the Fair Housing Accessibility Guidelines (FHAG) and the 2010 Standard for Accessible Design referenced by the American's with Disabilities Act (ADA) and the Architectural Barriers Act (ABA).

### **ANSI Approval**

This Standard was processed and approved for submittal to ANSI by the Accredited Standards Committee A117 on Architectural Features and Site Design of Public Buildings and Residential Structures for Persons with Disabilities. ANSI approved the 2017 edition on March 28, 2017. Committee approval of the Standard does not necessarily imply that all Committee members voted for its approval.

### **Adoption**

ICC A117.1–2017 is available for adoption and use by jurisdictions internationally. Its use within a governmental jurisdiction is intended to be accomplished through adoption by reference in accordance with proceedings establishing the jurisdiction's laws.

### Interpretations

Requests for interpretations on the provisions of ICC A117.1–2017 should be addressed to: ICC, Chicago District Office, 4051 W. Flossmoor Road, Country Club Hills, IL 60478–5795.

### Maintenance—Submittal of Proposals

All ICC standards are revised as required by ANSI. Proposals for revising this edition are welcome. Please visit the ICC website at <a href="https://www.iccsafe.org">www.iccsafe.org</a> for the official "Call for proposals" announcement. A proposal form and instructions can also be downloaded from <a href="https://www.iccsafe.org">www.iccsafe.org</a>.

ICC, its members and those participating in the development of ICC A117.1-2017 do not accept any liability resulting from compliance or noncompliance with the provisions of ICC A117.1-2017. ICC does not have the power or authority to police or enforce compliance with the contents of this standard. Only the governmental body that enacts this standard into law has such authority.

### **Marginal Markings**

Solid vertical lines in the margins within the body of the standard indicate a technical change from the requirements of the 2009 edition. Deletion indicators in the form of an arrow ( ) are provided in the margin where an entire section, paragraph, exception or table has been deleted or an item in a list of items or a table has been deleted.

# Accredited Standards Committee A117 on Architectural Features and Site Design of Public Buildings and Residential Structures for Persons with Disabilities

At the time of ANSI approval, the A117.1 Committee consisted of the following members:

| Chair  | . Gina Hilberry, AIA  |
|--|---|
| Organizational Member  | Representative  |
| Accessibility Equipment Manufacturers Association (AEMA) (PD)                            | . Scott A. Cleary<br>. Robert Murphy (Alt)  |
| American Council of the Blind (ACB) (CU)   | -   |
| American Hotel and Lodging Association (AHLA) (BO)                                       | . Douglas J. Anderson, CASp, RAS  |
| American Institute of Architects (AIA) (P)   |   |
| American Occupational Therapy Association (AOTA) (P)                                     | . Shoshana Shamberg, OTR, MS, FAOTA . Brian J. Dudgeon (Alt)                        |
| American Society of Interior Designers (ASID) (P)  |   |
| American Society of Plumbing Engineers (ASPE) (P)  |   |
| American Society of Safety Engineers (ASSE) (P)  |   |
|  | . R. Duane Wilson, ASTC . William Conner, ASTC (Alt) . Scott Crossfield, ASTC (Alt) |
| Association of Pool and Spa Professionals (APSP) (PD)                                    | . John Caden<br>. Carvin DiGiovanni (Alt)   |
| Association for Education & Rehabilitation of the Blind & Visually Impaired (AERBVI) (P) |   |
| Brain Injury Association of America (BIAA) (CU)  | •   |
| Builders Hardware Manufacturers Association, Inc. (BHMA) (PD)                            | . Michael Tierney<br>. Kurt A. Roeper (Alt)   |
| Building Owners and Managers Association International (BOMA) (BO)                       | . Steve Orlowski  |

### COMMITTEE

| Construction Specifications Institute (CSI)(P)                                       | . Dennis J. Hall, FAIA, FCSI  |
|--|---|
| Disability Rights Education & Defense Fund (DREDF) (CU)                              | . Marilyn Golden<br>. Karen L. Braitmayer, FAIA (Alt)                               |
| Hearing Loss Association of America (HLAA) (CU)                                      | •   |
|  | . Greg Guarnaccia<br>. Robert Dupuy (Alt)<br>. Eunice Noell-Waggoner (Alt)          |
|  | . John Paul Scott, AIA, NCARB<br>. Robert Minnick, PE, CSP<br>. Stephanie See (Alt) |
| International Code Council (ICC) (R)   | •   |
| International Sign Association (ISA) (PD)  | . Glenn Dea, AIA (Alt)  |
| Little People of America, Inc. (LPA) (CU)  | . Allison Lourash   |
| Montgomery County Department of Permitting Services (MCDPS) (R)                      | . Robert Kelly<br>. Hemal Mustafa (Alt)   |
| National Association of Convenience Stores (NACS) (BO)                               | . Bradley Gaskins, AIA, CASp<br>. Sean Robinson (Alt)                               |
| National Association of Home Builders (NAHB) (BO)                                    | . Dan Buuck.<br>. Gary Ehrlich, P.E. (Alt)  |
| National Association of Theater Owners   |   |
| National Association of the Deaf (NAD) (CU)  | . Hansel Bauman   |
| National Electrical Manufacturers Association (NEMA) (PD)                            | . Richard Roberts<br>. Denise Pappas (Alt)  |
| National Elevator Industry, Inc. (NEII) (PD)   | . Kevin L. Brinkman   |
| National Fire Protection Association (NFPA) (R)                                      |   |
| National Multifamily Housing Council (NMHC) (BO)                                     | . Ronald G. Nickson   |
| New Mexico Governor's Commission on Disability (NMGCD) (CU)                          | . Hope Reed<br>. Daniel A. Fernandez (Alt)  |
| North Carolina Department of Insurance; Office of the State Fire Marshal (NCOSFM)(R) | . Laurel W. Wright  |
| Paralyzed Veterans of America (PVA) (CU)   |   |

| Plumbing Manufacturers International (PMI) (PD)                                 |
|---|
| Rehabilitation Engineering and Assistive Technology of North America (RESNA)(R) |
| Society for Experiential Graphic Design (SEGD) (P)                              |
| Stairbuilders and Manufacturers Association (SMA) (PD)                          |
| Target Corporation (BO)   |
| United Cerebral Palsy Association, Inc. (UCPA) (CU)                             |
| United Spinal Association (CU)  |
| U.S. Access Board (USAB) (R)  |
| U.S. Department of Agriculture (USDA) (R)                                       |
| U.S. Department of Housing and Urban Development (HUD) (R)                      |
| Washington Association of Building Officials (WABO) (R)                         |
| World Institute on Disability (WID) (CU)  |

### **Individual Members**

Todd Andersen AIA (P) Alan Gettelman (PD) Jake L. Pauls, CPE (P) Ed Roether (P) John P. S. Salmen, FAIA (P) Kenneth M. Schoonover, PE (P)

### Acknowledgment

The updating of this standard over the past 6 years could only be accomplished by the hard work of not only the current committee members listed at the time of approval but also the many committee members who participated and contributed to the process over the course of development. ICC recognizes their contributions as well as those of the participants who, although not on the committee, provided valuable input during this update cycle.

The A117.1 standard committee would like to take a moment to recognize three members of the committee who were unable to see the fruits of their labor from this past cycle come to completion. Much of what has been accomplished would not have been possible without their contributions, expertise and passion for providing access to the disabled communities in the built environment. This edition of the standard will be a lasting tribute to their memory and a reminder for those who serve on the committee of what may be accomplished.

Brian D. Black – National Elevator Industry, Inc. Ron Burton – Building Operators and Managers Association Tricia Mason – Little People of America

### **Interest Categories**

**Builder/Owner/Operator** (**BO**) – Members in this category include those in the private sector involved in the development, construction, ownership and operation of buildings or facilities; and their respective associations.

Consumer/User (CU) – Members in this category include those with disabilities, or others who require accessibility features in the built environment for access to buildings, facilities and sites; and their respective associations.

**Producer/Distributor (PD)** – Members in this category include those involved in manufacturing, distributing, or sales of products; and their respective associations.

**Professional (P)** – Members in this category include those qualified to engage in the development of the body of knowledge and policy relevant to their area of practice, such as research, testing, consulting, education, engineering or design; and their respective associations.

**Regulatory** (**R**) – Members in this category include federal agencies, representatives of regulatory agencies or organizations that promulgate or enforce codes or standards; and their respective associations.

**Individual Expert (IE)** (Nonvoting) – Members in this category are individual experts selected to assist the consensus body. Individual experts shall serve for a renewable term of one year and shall be subject to approval by vote of the consensus body. Individual experts shall have no vote.

### **Voting Membership in Each Category**

| •                             | 0 ,               |
|-------------------------------|-------------------|
| Category                      | Number            |
| Builder/Owner/Operator - (BO) | 8                 |
| Consumer/User - (CU)          | 11                |
| Professional - (P)            | 15 (5 individual) |
| Producer/Distributor - (PD)   | 9 (1 individual)  |
| Regulatory - (R)              | 9                 |
| TOTAL MEMBERS                 | 52                |

### **Table of Contents**

| СНА               | PTER 1 APPLICATION AND ADMINISTRATION     | 1  | CHA | PTER 5   | GENERAL SITE AND BUILDING ELEMENTS      | 55        |
|-------------------|---|----|-----|----------|---|-----------|
| 101               | Title                                     | 1  | 501 | General  |   | 55        |
| 102               | Purpose                                   | 1  | 502 | Parking  | Spaces                                  | 55        |
| 103               | Human Factor Provisions                   | 1  | 503 | Passeng  | ger Loading Zones                       | 59        |
| 104               | Compliance Alternatives                   | 1  | 504 | Stairwa  | ys                                      | 60        |
| 105               | Conventions                               | 1  | 505 | Handra   | ils                                     | 62        |
| 106               | Referenced Documents                      | 1  | 506 | Windov   | vs                                      | 65        |
| 107               | Definitions                               | 3  | 507 | Accessi  | ble Routes through Parking              | 65        |
| СНА               | PTER 2 SCOPING                            | 7  | CHA | PTER 6   | PLUMBING ELEMENTS AND                   | <b>(5</b> |
| 201               | General                                   | 7  | 601 |          | FACILITIES                              |           |
| 202               | Dwelling and Sleeping Units               | 7  | 601 |          | F                                       |           |
| 203               | Administration                            | 7  | 602 |          | g Fountains and Bottle Filling Stations |           |
| СПУ               | PTER 3 BUILDING BLOCKS                    | 0  | 603 |          | nd Bathing Rooms                        |           |
| 301               | General                                   |    | 604 |          | Closets and Toilet Compartments         |           |
| 302               | Floor Surfaces                            |    | 605 |          |   |           |
| 303               | Changes in Level                          |    | 606 |          | ies and Sinks                           |           |
|                   |   |    | 607 |          | S                                       |           |
| 304               | Turning Space                             |    | 608 |          | Compartments                            |           |
| 305               | Clear Floor Space                         |    | 609 |          | ars                                     |           |
| 306               | Knee and Toe Clearance                    |    | 610 |          | . W. 1 1 (I. d D                        |           |
| 307               | Protruding Objects                        |    | 611 |          | g Machines and Clothes Dryers           |           |
| 308               | Reach Ranges                              |    | 612 | Saunas   | and Steam Rooms                         | 92        |
| 309<br><b>CHA</b> | Operable Parts  PTER 4 ACCESSIBLE ROUTES  |    | CHA | PTER 7   | COMMUNICATION ELEMENTS A FEATURES       |           |
| 401               | General                                   | 19 | 701 | General  |   | 93        |
| 402               | Accessible Routes                         | 19 | 702 | Alarms   |   | 93        |
| 403               | Walking Surfaces                          | 19 | 703 | Signs    |   | 93        |
| 404               | Doors, Doorways and Gates                 |    | 704 | Telepho  | ones                                    | 100       |
| 405               | Ramps                                     |    | 705 | Detecta  | ble Warnings and Surfaces               | 101       |
| 406               | Curb Ramps and Blended Transitions        | 35 | 706 | Assistiv | ve Listening Systems                    | 106       |
| 407               | Elevators                                 |    | 707 | Automa   | atic Teller Machines (ATMs) and Fare    |           |
| 408               | Limited-use/Limited-application Elevators |    |     |          | nes                                     |           |
| 409               | Private Residence Elevators               |    | 708 | Two-wa   | ay Communication Systems                | 108       |
| 410               | Platform Lifts                            | 51 |     |          |   |           |

### TABLE OF CONTENTS

| CHA        | PTER 8 SPECIAL ROOMS AND SPACES109     | 1002         | Amusement Rides                                 | 127 |
|------------|--|--------------|---|-----|
| 801        | General                                | 1003         | Recreational Boating Facilities                 | 129 |
| 802        | Assembly Areas                         | 1004         | Exercise Machines and Equipment                 | 129 |
| 803        | Dressing, Fitting, and Locker Rooms116 | 1005         | Fishing Piers and Platforms                     | 131 |
| 804        | Kitchens116                            | 1006         | Golf Facilities                                 | 132 |
| 805        | Transportation Facilities              | 1007         | Miniature Golf Facilities                       | 132 |
| 806        | Holding Cells and Housing Cells121     | 1008         | Play Areas                                      | 133 |
| 807<br>808 | Courtrooms                             | 1009         | Swimming Pools, Wading Pools, Hot Tubs and Spas | 137 |
|            |  | 1010         | Shooting Facilities with Firing Positions       | 142 |
| CHA        | PTER 9 FURNISHINGS AND EQUIPMENT . 123 |              |   |     |
| 901        | General                                | CHAI<br>UNIT | PTER 11 DWELLING UNITS AND SLEEPI<br>S          |     |
| 902        | Dining Surfaces and Work Surfaces123   | 1101         | General   |     |
| 903        | Benches                                | 1102         | Accessible Units                                |     |
| 904        | Sales and Service Counters and Windows |              |   |     |
| 905        | Storage Facilities                     | 1103         | Type A Units                                    |     |
| 906        | Charging Stations                      | 1104         | Type B Units                                    |     |
| 907        | Gaming Machines and Tables126          | 1105         | Type C (Visitable) Units                        | 159 |
| 707        | Guilling Practition and Paoles         | 1106         | Units with Communication Features               | 160 |
| CHAI       | PTER 10 RECREATIONAL FACILITIES 127    | INDE         | X   | 161 |
| 1001       | General                                |              |   | 101 |

### **List of Figures**

| Chapter 1                       | Application and Administration 1                                  | Figure 308.2.2       | Obstructed High Forward Reach 16   |
|---------------------------------|---|----------------------|--|
| Figure 105.4                    | Graphic Convention for Figures2                                   | Figure 308.3.1       | Unobstructed Side Reach  |
|                                 |   | Figure 308.3.2(A)    | Obstructed High Side Reach 17  |
| Chapter 2                       | Scoping (No figures)  | Figure 308.3.2(B)    | Obstructed High Side Reach 17  |
|                                 |   | Figure 309.1         | Operable Parts - Exception 3 18  |
| Chapter 3                       | Building Blocks 9   |                      |  |
| Figure 302.2                    | Carpet on Floor Surfaces 9  | Chapter 4. Accessi   | ble Routes   |
| Figure 302.3                    | Openings in Floor Surfaces 9                                      | Figure 403.5.1(A)    | Clear Width of an Accessible   |
| Figure 303.2                    | Vertical Change in Level 9  |                      | Route - New Buildings - Interior 19  |
| Figure 303.3                    | Beveled Changes in Level9   | Figure 403.5.1(B)    | Clear Width of an Accessible<br>Route - New Buildings - Exterior 20              |
| Figure 304.3.1.1                | Buildings - Size and Overlap 10                                   | Figure 403.5.1(C)    | Clear Width of an Accessible Route - Existing Buildings - Interior 20            |
| Figure 304.3.1.2                | Circular Turning Space - Existing Buildings - Size and Overlap 10 | Figure 403.5.1(D)    | Clear Width of an Accessible   |
| Figure 304.3.2.1                | (A) T-Shaped Turning Space - New Buildings - Option 110           | Figure 403.5.2.1(A)  | Route - Existing Buildings - Exterior 20<br>Clear Width at 180-degree Turn - New |
| Figure 304.3.2.1                | (B) T-shaped Turning Space - New Buildings - Option 211           | Figure 403.5.2.1(B)  | Buildings - Option 1   |
| Figure 304.3.2.1                |   |                      | Buildings - Option 2 21  |
| E' 2042.2.1                     | New Buildings - Option 3  | Figure 403.5.2.1(C)  | Clear Width at 180-degree Turn - New Buildings - Option 3                        |
| Figure 304.3.2.1                | New Buildings - Overlap   | Figure 403.5.2.2(A)  | Clear Width at 180-degree Turn - Existing Buildings                              |
| Figure 304.3.2.2                | T-shaped Turning Space - New Buildings - Size and Overlap 12      | Figure 403.5.2.2(B)  | Clear Width at 180-degree Turn - Existing  |
| Figure 304.3.2.2                | .1 T-shaped Turning Space - Existing Buildings - Overlap          | Figure 403.5.3.1(A)  | Buildings - Exception  |
| Figure 305.3.1                  | Size of Clear Floor Space - New Buildings                         | Figure 403.5.3.1(B)  | Buildings - Option 1   |
| Figure 305.3.2                  | Size of Clear Floor Space - Existing Buildings                    | Figure 403.5.3.1(C)  | Buildings - Option 2   |
| Figure 305.5(A)                 | Position of Clear Floor Space -                                   | Figure 403.5.3.1(D)  | Buildings - Option 3   |
| Figure 305.5(B)                 | Forward   | 8                    | Buildings - Option 4 23  |
|                                 | Parallel  | Figure 403.5.3.2     | Clear Width at 90-degree Turn - Existing Buildings                               |
| Figure 305.7.1                  | Alcove - Parallel Approach  | Figure 403.5.4.1(A)  | Passing Space- New Buildings - 60 X 60 Option24                                  |
| Figure 305.7.2                  | Maneuvering Clearance in an Alcove - Forward Approach13           | Figure 403.5.4.1(B)  | Passing Space- New Buildings - T-turn Option                                     |
| Figure 306.2(A)                 | Toe Clearance - Elevation   | Figure 403.5.4.2(A)  | Passing Space- Existing  |
| Figure 306.2(B)                 | Toe Clearance - Plan14  | 118010 100101112(11) | Buildings - 60 X 60 Option25   |
| Figure 306.3(A) Figure 306.3(B) |   | Figure 403.5.4.2(B)  | Passing Space- Existing Buildings - T-turn Option                                |
| Figure 307.2                    | Limits of Protruding Objects 15                                   | Figure 404.2.2(A)    | Clear Width of Doorways - Hinged   |
| Figure 307.3(A)                 | Post-mounted Protruding Objects 15                                | 8                    | Door   |
| Figure 307.3(B)                 | Post-mounted Protruding Objects 15                                | Figure 404.2.2(B)    | Clear Width of Doorways - Sliding  |
| Figure 307.4                    | Reduced Vertical Clearance 16                                     |                      | Door   |
| Figure 308.2.1                  | Unobstructed Forward Reach16                                      | Figure 404.2.2(C)    | Clear Width of Doorways - Folding Door   |

### LIST OF FIGURES

| Figure 404.2.2(D)     | Clear Width of Doorways-<br>Doorways within Doors 26   | Figure 404.2.3.5(A)                                    | Recessed Doors and Gates - New Buildings - Pull Side   |
|-----------------------|--|--|--|
| Figure 404.2.3.2(A)   | Maneuvering Clearances at Manual<br>Swinging Doors - Front Approach -                                    | Figure 404.2.3.5(B)                                    | Recessed Doors and Gates - New Buildings - Push Side   |
| Figure 404.2.3.2(B)   | Pull Side  | Figure 404.2.3.5(C)                                    | Recessed Doors and Gates - New Buildings - Push Side - Provided with Both Closer and Latch                   |
| Figure 404.2.3.2(C)   | Push Side - New Buildings 26  Maneuvering Clearances at Manual   | Figure 404.2.3.5(D)                                    | Recessed Doors and Gates - Existing Buildings - Pull Side  |
|                       | Swinging Doors - Front Approach - Pull Side - Existing Buildings -                                       | Figure 404.2.3.5(E)                                    | Recessed Doors and Gates - Existing Buildings - Push Side30  |
| Figure 404.2.3.2(D)   | Footnote 5   | Figure 404.2.3.5(F)                                    | Recessed Doors and Gates - Existing<br>Buildings - Push Side - Door<br>Provided with Both Closer and Latch30 |
| Figure 404.2.3.2(E)   | Maneuvering Clearances at Manual Swinging Doors - Hinge Approach -                                       | Figure 404.2.5(A)                                      | Two Doors or Gates in a Series - New Buildings   |
| Figure 404.2.3.2(F)   | Pull Side  | Figure 404.2.5(B)                                      | Two Doors or Gates in a Series - New Buildings   |
| rigule 404.2.3.2(r)   | Swinging Doors - Hinge Approach - Push Side  | Figure 404.2.5(C)                                      | Two Doors or Gates in a Series - New Buildings   |
| Figure 404.2.3.2(G)   | Maneuvering Clearances at Manual<br>Swinging Doors - Latch Approach -                                    | Figure 404.2.5(D)                                      | Two Doors or Gates in a Series - Existing Buildings31  |
| Figure 404.2.3.2(H)   | Pull Side  | Figure 404.2.5(E)                                      | Two Doors or Gates in a Series - Existing Buildings  |
| 11guie 10 1.2.5.2(11) | Swinging Doors - Latch Approach - Push Side  | Figure 404.2.5(F)                                      | Two Doors or Gates in a Series - Existing Buildings  |
| Table 404.2.3.2       | Maneuvering Clearances at Manual Swinging Doors and Gates  | Table 405.2  | Allowable Ramp Dimensions for Construction in Existing Sites, Buildings and Facilities33                     |
| Table 404.2.3.3       | Maneuvering Clearances at Sliding and Folding Doors  | Figure 405.7   | Ramp Landings  |
| Figure 404.2.3.3(A)   | Maneuvering Clearance at Sliding and Folding Doors - Front Approach - New Buildings                      | Figure 405.9   | Edge Protection - Limited Drop Off - Exception 3   |
| Figure 404.2.3.3(B)   | Maneuvering Clearance at Sliding and Folding Doors - Front Approach - Existing Buildings - Footnote 2 28 | Figure 405.9.1<br>Figure 405.9.2.1<br>Figure 405.9.2.2 | Curb.       .35         Barrier       .35  |
| Figure 404.2.3.3(C)   | Maneuvering Clearance at Sliding and Folding Doors - Pocket or   | Figure 406.2(A) Figure 406.2(B) Figure 406.3(A)        | Perpendicular Curb Ramp36 Perpendicular Curb Ramp36 Parallel Curb Ramp37                                     |
| Figure 404.2.3.3(D)   | Hinge Approach   | Figure 406.3(B)<br>Figure 406.4                        | Parallel Curb Ramp   |
| Table 404.2.3.4       | Maneuvering Clearances for Doorways without Doors or Gates 29  | Figure 406.5.2<br>Figure 406.5.4                       | Grade Break  |
| Figure 404.2.3.4(A)   | Maneuvering Clearances for<br>Doorways without Doors or Gates -  | Figure 406.5.5   | Curb Ramps   |
| Figure 404.2.3.4(B)   | Front Approach - New Buildings 29  Maneuvering Clearances for  | Figure 407.2.1.1                                       | Height of Elevator Call Buttons 41   |
| 1 1guil 101.2.3.1(D)  | Doorways without Doors or Gates -<br>Front Approach - Existing Buildings -                               | Figure 407.2.1.7                                       | Destination-oriented Elevator Indication   |
| Figure 404.2.3.4(C)   | Footnote 1   | Figure 407.2.2.2(A)                                    | Elevator Visible Signals - Height of Signals   |
| _ , , ,               | Doorways without Doors or Gates - Side Approach  | Figure 407.2.2.2(B)                                    | Elevator Visible Signals - Size of Signals   |

| Figure 407.2.3.1   | Floor Designation   | Figure 410.5.1.1  | Platform Lifts - Size with Single Door or                                  |
|--------------------|---|-------------------|--|
| Figure 407.2.3.2   | Destination-oriented Elevator Car Identification  |                   | Doors on Opposite Ends - New Buildings                                     |
| Figure 407.4.1(A)  | Inside Dimensions of Elevator Cars -<br>Centered Door Location  | Figure 410.5.1.2  | Platform Lifts - Size with Door or<br>Doors on Opposite Ends -             |
| Figure 407.4.1(B)  | Inside Dimensions of Elevator Cars -<br>Side (Off-centered Door) Location 44                                  | Figure 410.5.2.1  | Existing Buildings   |
| Figure 407.4.1(C)  | Inside Dimensions of Elevator Cars - Any Door Location  | Figure 410.5.2.2  | Platform Lifts - Size with Doors on Adjacent Sides - Existing Buildings 53 |
| Figure 407.4.1(D)  | Inside Dimensions of Elevator Cars - Any Door Location  | Charles 5 Carren  |  |
| Figure 407.4.1(E)  | Inside Dimensions of Elevator Cars -  | -                 | Il Site and Building Elements  |
| T 11 407 4 1       | Existing Car Configuration  | Figure 502.2(A)   | Vehicle Parking Space Size   |
| Table 407.4.1      | Minimum Dimensions of Elevator Cars   | Figure 502.2(B)   | Van Parking Space Size Exception 55  |
| Figure 407.4.6.2   | Elevator Car Control Buttons  | Figure 502.4      | Parking Space Access Aisle   |
| Table 407.4.7.1.4  | Control Button Identification   | Figure 502.9.1    | Wide Sidewalks   |
| Figure 408.3.3(A)  | Door Location for Limited Use/  | Figure 502.9.1.2  | Narrow Sidewalks   |
| Figure 406.3.3(A)  | Limited Application (LULA) Elevators - Car with Single Door 48  | Figure 502.9.2    | Perpendicular or Angled Parking Space58                                    |
| Figure 408.3.3(B)  | Door Location for Limited Use/Limited Application (LULA) Elevators -  | Figure 503.3(A)   | Passenger Loading Zone<br>Access Aisle - New Buildings 59                  |
| E' 400.2.2(G)      | Car with Doors on Opposite Sides 48   | Figure 503.3(B)   | Passenger Loading Zone Access Aisle - Existing Buildings 60                |
| Figure 408.3.3(C)  | Door Location for Limited Use/Limited Application (LULA) Elevators -  | Figure 504.2      | Treads and Risers for Stairways 60   |
| Eigung 408 2 2(D)  | Car with Doors on Adjacent Sides 48   | Figure 504.5(A)   | Stair Nosings - Vertical Riser - Curve or Bevel at Leading Edge61          |
| Figure 408.3.3(D)  | Door Location for Limited Use/Limited<br>Application (LULA) Elevators -<br>Car with Doors on Adjacent Sides - | Figure 504.5(B)   | Stair Nosings - Vertical Riser - Curved Nosing                             |
| Figure 408.4.1(A)  | Exception   | Figure 504.5(C)   | Stair Nosings - Vertical Riser - Beveled Nosing                            |
| Figure 406.4.1(A)  | Limited Application (LULA) Elevator Cars - New Buildings  | Figure 504.5(D)   | Stair Nosings - Vertical Riser - Angled Riser                              |
| Figure 408.4.1(B)  | Inside Dimensions of Limited Use/   | Figure 505.4(A)   | Handrail Height - Stairs 62  |
| 8(-)               | Limited Application (LULA) Elevator   | Figure 505.4(B)   | Handrail Height - Ramps 62   |
|                    | Cars - Existing Buildings -   | Figure 505.5      | Handrail Clearance   |
|                    | Exception 1   | Figure 505.7(A)   | Handrail Cross Section - Circular 63                                       |
| Figure 408.4.1(C)  | Inside Dimensions of Limited Use/   | Figure 505.7(B)   | Handrail Cross Section - Noncircular . 63                                  |
|                    | Limited Application (LULA) Elevator<br>Cars - Existing Buildings -  | Figure 505.7(C)   | Handrail Cross Section - Noncircular . 63                                  |
|                    | Exception 250   | Figure 505.10.1   | Top and Bottom Handrail  |
| Figure 409.4.1(A)  | Private Residence Elevators - New Buildings - Car Size 50   | -                 | Extension at Ramps 64  |
| Figure 409.4.1(B)  | Private Residence Elevators - Existing  | Figure 505.10.2   | Top Handrail Extension at Stairs 64  |
| Figure 409.4.6.3   | Buildings - Car Size  | Figure 505.10.3   | Bottom Handrail Extension at Stairs64                                      |
| 11guic 409.4.0.5   | Residence Elevators   | CI ( C DI 1)      |  |
| Figure 410.2.1(A)  | Platform Lift Doors and Gates - Platform  | _                 | ing Elements and Facilities 67   |
| 118010 1101211(11) | Lift with Door at One End or at Opposite Ends   | Figure 602.2.1(A) | Clear Floor Space at Wheelchair Drinking Fountains67                       |
| Figure 410.2.1(B)  | Platform Lift Doors and Gates - Platform<br>Lift with Doors on Adjacent Sides 52                              | Figure 602.2.1(B) | Clear Floor Space at Wheelchair Drinking Fountains - Primarily for         |
|                    |   | Figure 602.2.3    | Children's Use - Exception   |

### LIST OF FIGURES

| Figure 602.2.4      | Wheelchair Drinking Fountain Spout Location   | Figure 604.11.7(B)  | Children's Dispenser Outlet - Exception                                |
|---------------------|---|---------------------|--|
| Figure 602.3.2      | Standing Use Drinking Fountain Spout Height and Location 68   | Figure 605.2(A)     | Height and Depth of Urinal - Wall Hung Type                            |
| Figure 602.3.3      | Standing Use Drinking Fountain Spout Location 68  | Figure 605.2(B)     | Height and Depth of Urinal - Stall Type79                              |
| Table 603.6         | Maximum Reach Depth and   | Figure 606.3        | Height of Lavatories and Sinks79                                       |
|                     | Height 69   | Figure 607.2(A)     | Clearance for Bathtubs with Removable                                  |
| Figure 604.2        | Water Closet Location 69  |                     | In-tub Seats   |
| Figure 604.3        | Size of Clearance for Water Closet70  | Figure 607.2(B)     | Clearance for Bathtubs with Seat at Head End of Tub80                  |
| Figure 604.4        | Water Closet Seat Height 70   | Figure 607.4.1(A)   | Grab Bars for Bathtubs with  |
| Figure 604.5.1      | Side-Wall Grab Bar for Water Closet   | Figure 607.4.1(B)   | Seat at Head End of Tub - Elevation81  Grab Bars for Bathtubs with     |
| Figure 604.5.2      | Rear-Wall Grab Bar for  |                     | Seat at Head End of Tub - Plan81                                       |
|                     | Water Closet  | Figure 607.4.2(A)   | Grab Bars for Bathtubs with Removable Seats - Elevation 81             |
| Figure 604.7.1(A)   | Dispenser Outlet Location - Protruding Dispenser Below Grab Bar   | Figure 607.4.2(B)   | Grab Bars for Bathtubs   |
| Figure 604.7.1(B)   | Dispenser Outlet Location - Protruding  | 1 iguic 007.4.2(D)  | with Removable Seats - Plan82  |
| riguie oo ii.i.i(B) | Dispenser Above Grab Bar 72   | Figure 607.5        | Location of Bathtub Controls 82  |
| Figure 604.7.1(C)   | Dispenser Outlet Location - Recessed  | Figure 608.2.1.1    | Transfer-type Shower Compartment                                       |
|                     | Dispenser   |                     | Size82   |
| Figure 604.7.1(D)   | Dispenser Outlet Location - Dispenser in Front of Water Closet - Exception 73                           | Figure 608.2.1.2(A) | Transfer-type Shower Compartment<br>Clearances - New Buildings -       |
| Figure 604.9.2(A)   | Wheelchair Toilet Compartments - Wall   | E' (00.2.1.2/D)     | Option 1   |
| Figure 604.9.2(B)   | Hung Closet, Adult  | Figure 608.2.1.2(B) | Transfer-type Shower Compartment Clearances - New Buildings - Option 2 |
|                     | Mounted Water Closet, Adult - Wall<br>Hung and Floor Mounted Water<br>Closet, Children                  | Figure 608.2.1.2(C) | Transfer-type Shower Compartment<br>Clearances - Existing Buildings 83 |
| Figure 604.9.2.3    | Wheelchair Toilet Compartments -  | Figure 608.2.2.1    | Standard Roll-in-type Shower   |
| 118410 00 1171210   | Alternate Wheelchair Toilet   | 118010 000.2.2.1    | Compartment Size83   |
|                     | Compartment74   | Figure 608.2.2.2    | Standard Roll-in-type Shower   |
| Figure 604.9.3(A)   | Wheelchair Toilet Compartment Doors -<br>Door Swinging into the Wheelchair                              |                     | Compartment Clearance  |
|                     | Toilet Compartment  | Figure 608.2.3.1    | Alternate Roll-in-type Shower Compartment Size84                       |
| Figure 604.9.3(B)   | Wheelchair Toilet Compartment Doors -   | Figure 608.3.1(A)   | Grab Bars in Transfer-type Shower -                                    |
|                     | Exception 3 - Alternate Wheelchair  | 1 15410 000.5.1(11) | Elevation  |
| E' (04.0.2.1(A)     | Compartment   | Figure 608.3.1(B)   | Grab Bars in Transfer-type Shower -                                    |
| Figure 604.9.3.1(A) | Wheelchair Toilet Compartment Door<br>Opening Location - Door Swinging in                               |                     | Plan   |
| Eigurg 604 0 2 1/D) | on Front Wall of Partition  | Figure 608.3.2(A)   | Grab Bars in Standard Roll-in-type Shower - Elevation                  |
| Figure 604.9.3.1(B) | Wheelchair Toilet Compartment Door<br>Opening Location - Door Swinging in<br>on Side Wall of Partitions | Figure 608.3.2(B)   | Grab Bars in Standard Roll-in-type<br>Shower - Plan                    |
| Table 604.9.3.1     | Door Opening Location   | Figure 608.3.3(A)   | Grab Bars in Alternate Roll-in-type                                    |
| Figure 604.9.5(A)   | Toe Clearance - Elevation   |                     | Shower - Elevation   |
| Figure 604.9.5(B)   | Toe Clearance - Plan  | Figure 608.3.3(B)   | Grab Bars in Alternate Roll-in-type Shower - Plan                      |
| Figure 604.10.1     | Ambulatory Compartment  | Figure 608.4.1      | Transfer-type Shower Controls and                                      |
| Figure 604.11.2     | Children's Water Closet Location 77   | 1 15410 000.7.1     | Hand Shower Location   |
| Figure 604.11.4     | Children's Water Closet Height 77   | Figure 608.4.2      | Standard Roll-in-type Shower   |
| Figure 604.11.7(A)  | Children's Dispenser Outlet - Location  |                     | Controls and Hand Shower Location86                                    |

| Figure 608.4.3(A)                 | Alternate Roll-in-type Shower Controls and Hand Shower Location - End Wall - | Figure 704.2.1.2  | Clear Floor Space for Telephones -<br>Forward Approach                          |
|-----------------------------------|--|-------------------|---|
| Figure 608.4.3(B)                 | Elevation  | Figure 705.5(A)   | Truncated Dome Size and Spacing102  |
|                                   | and Hand Shower Location - Control   | Figure 705.5(B)   | Elevation (Enlarged) 102  |
| Figure 609.2                      | Wall - Elevation       87         Size of Grab Bars       88                 | Figure 705.6(A)   | Extent of Detectable Warnings - Perpendicular                                   |
| Figure 609.3<br>Figure 609.4.2(A) | Spacing of Grab Bars   | Figure 705.6(B)   | Extent of Detectable Warnings - Returned Curb                                   |
| Figure 609.4.2(B)                 | Side-wall View   | Figure 705.6(C)   | Extent of Detectable Warnings - Parallel  |
|                                   | Rear-wall View89   | Figure 705.7.1    | Perpendicular Curb Ramps 104  |
| Figure 610.2(A)                   | Bathtub Seats - Removable In-tub Seats                                       | Figure 705.7.2    | Parallel Curb Ramps   |
| Figure 610.2(B)                   | Bathtub Seats - Seat Provided at Head  | Figure 705.7.3    | Blended Transitions 105   |
| rigule 010.2(B)                   | End of Tub   | Figure 705.7.4    | Pedestrian Refuge Islands 106   |
| Figure 610.3.1                    | Rectangular Shower Compartment   | Figure 705.7.5    | Pedestrian At-grade Rail Crossings 106  |
|                                   | Seats  | Figure 707.5(A)   | Numeric Key Layout - 12-key   |
| Figure 610.3.2                    | L-shaped Shower Compartment Seats . 90                                       | E' 505 5 (D)      | Ascending   |
| Figure 611.2(A)                   | Clear Floor Space - Top Loading 91   | Figure 707.5(B)   | Numeric Key Layout - 12-key Descending107                                       |
| Figure 611.2(B)                   | Clear Floor Space - Front Loading 91   | Table 707.6.1     | Raised Symbols  |
| Figure 611.4 (A)                  | Height of Laundry Equipment - Top Loading                                    |                   | Rooms and Spaces 109  |
| Figure 611.4 (B)                  | Height of Laundry Equipment -  | Figure 802.3(A)   | •   |
|                                   | Front Loading  | Figure 802.5(A)   | Width of Wheelchair Space in Assembly Area - Single Space 109                   |
| _                                 | unication Elements and Features 93   | Figure 802.3(B)   | Width of Wheelchair Space in<br>Assembly Area - Multiple Adjacent               |
| Γable 703.2.4                     | Visual Character Height 94   |                   | Space   |
| Figure 703.3.5<br>Figure 703.3.10 | Character Height   | Figure 802.4(A)   | Depth of Wheelchair Space in<br>Assembly Area - Front or Rear Access -          |
| El =00.011                        | above Floor  | TI 000 4/D)       | New Buildings   |
| Figure 703.3.11                   | Location of Signs at Doors   | Figure 802.4(B)   | Depth of Wheelchair Space in<br>Assembly Area - Front or Rear Access -          |
| Figure 703.4.3                    | Braille Measurement  |                   | Existing Buildings 109  |
| Γable 703.4.3                     | Braille Dimensions   | Figure 802.4(C)   | Depth of Wheelchair Space in Assembly   |
| Figure 703.4.4<br>Figure 703.4.5  | Position of Braille  |                   | Area - Side Access - New and Existing Buildings109                              |
| E' 702.5                          | above Floor  | Figure 802.5.1(A) | Wheelchair Space Location Overlap -   |
| Figure 703.5                      | Pictogram Field  |                   | Rear Approach - New and   |
| Figure 703.6.3.1                  | International Symbol for Accessibility                                       | Figure 802.5.1(B) | Existing Buildings  |
| Figure 703.6.3.2                  | International TTY Symbol 98  |                   | Side Approach   |
| Figure 703.6.3.3                  | International Symbol of Access for Hearing Loss                              | Figure 802.7.2(A) | Companion Seat Alignment - Elevation  |
| Figure 703.6.3.4<br>Table 703.7.4 | Volume-controlled Telephone 98  Low Resolution VMS Character                 | Figure 802.7.2(B) | Companion Seat Alignment - Front or<br>Rear Approach - Existing Buildings . 112 |
|                                   | Height   | Figure 802.7.2(C) | Companion Seat Alignment - Front or<br>Rear Approach - New Buildings 112        |
| Гable 703.7.5                     | Pixel Count for Low Resolution VMS Signage                                   | Figure 802.7.2(D) | Companion Seat Alignment - Side Approach  |
| Figure 703.7.5                    | Low Resolution VMS Signage Characters  | Figure 802.9.1.1  | Lines of Sight over the Heads of  |
| Figure 704.2.1.1                  | Clear Floor Space for Telephones - Parallel Approach101                      |                   | Seated Spectators   |

### LIST OF FIGURES

| Figure 802.9.1.2    | Lines of Sight between the Heads of Seated Spectators               | Table 1008.3.2.1.2      | Number and Types of Ground<br>Level Play Components Required                      |
|---------------------|---|-------------------------|---|
| Figure 802.9.2      | Line of Sight over Standing   |                         | to be on Accessible Routes  |
|                     | Spectators  | Figure 1008.4.2.1       | Transfer Platforms  |
| Table 802.9.2.2     | Required Wheelchair Space Location                                  | Figure 1008.4.2.2       | Transfer Steps  |
|                     | Elevation over Standing Spectators                                  | Figure 1009.2.2         | Pool Lift Seat Location   |
| Table 802.10        | Wheelchair Space Location Dispersion                                | Figure 1009.2.3(A)      | Clear Deck Space at Pool Lifts - New Buildings                                    |
| Figure 804.2.1(A)   | Pass-through Kitchen Clearance 116                                  | Figure 1009.2.3(B)      | Clear Deck Space at Pool Lifts - Existing Buildings                               |
| Figure 804.2.1(B)   | Pass-through Kitchen Clearance 116                                  | Figure 1009.2.4         | Pool Lift Seat Height   |
| Figure 804.2.2(A)   | U-shaped Kitchen Clearance 117                                      | Figure 1009.2.8         | Pool Lift Submerged Depth   |
| Figure 804.2.2(B)   | U-shaped Kitchen Clearance 117                                      | Figure 1009.3.2         | Sloped Entry Submerged Depth 139  |
| Figure 804.2.2(C)   | U-shaped Kitchen Clearance -  | Figure 1009.3.3         | Handrails for Sloped Entry  |
|                     | Exception   | Figure 1009.4.1         | Clear Deck Space at Transfer  |
| Figure 805.2.2(A)   | Size of Bus Boarding and<br>Alighting Area - New Buildings 119      | _                       | Walls   |
| Figure 805.2.2(B)   | Size of Bus Boarding and  | Figure 1009.4.2         | Transfer Wall Height  |
|                     | Alighting Area - Existing Buildings . 119                           | Figure 1009.4.3         | Depth and Length of Transfer Walls  |
| Figure 805.3        | Bus Shelters  | Figure 1009.4.5         | Grab Bars for Transfer Walls 140  |
| Figure 805.10       | Track Crossing  | Figure 1009.5.1         | Size of Transfer Platforms  |
| Chapter 9. Furnishi | ngs and Equipment   | Figure 1009.5.2         | Clear Deck Space at Transfer Platforms  |
| Figure 903(A)       | Benches - Bench size and Clear                                      | Figure 1009.5.4         | Transfer Steps  |
|                     | Floor Space   | Figure 1009.5.6         | Size of Transfer Steps  |
| Figure 903(B)       | Benches - Bench Back Support and                                    | Figure 1009.5.7(A)      | Grab Bars - Individual Grab Bars 141  |
| <b>T</b>            | Seat Height   | Figure 1009.5.7(B)      | Grab Bars - Continuous Grab Bars 141  |
| Figure 904.3(A)     | Sales and Service Counters - Cross Section                          | 1 iguie 1009.3.7(D)     | Glab Bars Continuous Glab Bars  |
| Eigura 004 2(D)     | Sales and Service Counters -  | Chapter 11. Dwelling    | Units and Sleeping Units 143  |
| Figure 904.3(B)     | Elevation   | Figure 1103.11.2.4(A)   | Water Closets in Type A Units -   |
| Figure 904.4.2      | Height of Checkout Counters 126                                     | 1 iguie 1103.11.2.1(11) | Water Closet Location   |
|                     |   | Figure 1103.11.2.4(B)   | Water Closets in Type A Units -   |
| Chapter 10. Recreat | cional Facilities127  | E: 1102 11 2 4(C)       | Minimum Clearance   |
| Figure 1002.4.4.3   | Protrusions in Wheelchair Spaces in Amusement Rides                 | Figure 1103.11.2.4(C)   | Water Closets in Type A Units -<br>Clearance with Lavatory (Overlap<br>Exception) |
| Figure 1003.3.1(A)  | Boat Slip and Boarding Pier   | Figure 1103.11.2.4(D)   | Water Closets in Type A Units -   |
|                     | Clearance   | 1 iguie 1103.11.2.1(D)  | Water Closet Seat Height  |
| Figure 1003.3.1(B)  | Boat Slip and Boarding Pier<br>Clearance - Exception 1 - Clear Pier | Figure 1103.11.2.5.1(A) | Clearance for Bathtubs in Type A Units - With Removable Seat                      |
|                     | Space Reduction at Boat Slips and Boarding Piers                    | Figure 1103.11.2.5.1(B) | Clearance for Bathtubs in Type A  |
| Figure 1003.3.1(C)  | Boat Slip and Boarding Pier   | Eigung 1102 11 2 5 2    | Units - With Permanent Seat   |
|                     | Clearance - Exception 2 - Edge<br>Protection at Boat Slips and      | Figure 1103.11.2.5.2    | Standard Roll-in-type Shower Compartment in Type A Units 147                      |
| Figure 1005.4.2     | Boarding Pier   | Figure 1103.12.1.1      | Minimum Kitchen Clearance in Type A Units147                                      |
|                     | Fishing Piers and Platforms 131                                     | Figure 1103.12.1.2(A)   | U-shaped Kitchen Clearance in   |
| Figure 1007.3.2(A)  | Golf Club Reach Range - New Buildings                               |                         | Type A Units  |
| Figure 1007.3.2(B)  | Golf Club Reach Range -   | Figure 1103.12.1.2(B)   | U-shaped Kitchen Clearance in Type A Units - Exception                            |
| 1.5010 1001.3.2(D)  | Existing Buildings  |                         | 7,  |

| Figure 1103.12.3         | Work Surface in Kitchen for Type A Units148   |
|--------------------------|---|
| Figure 1103.12.4         | Kitchen Sink for Type A Units149  |
| Figure 1104.1.1          | Clear Floor Space for Type B Units150   |
| Figure 1104.9            | Reach over a Kitchen or Bathroom Cabinet  |
| Figure 1104.11.1.1       | Swing-up Grab Bars for<br>Water Closets   |
| Figure 1104.11.3.1.1     | Lavatory in Type B Units – Option A Bathrooms   |
| Figure 1104.11.3.1.2(A)  | Clearance at Water Closets in Type B Units - Water Closet Location $\dots 153$                  |
| Figure 1104.11.3.1.2(B)  | Clearance at Water Closets in Type B Units - Clearance Width and Depth $153$                    |
| Figure 1104.11.3.1.2(C)  | Clearance at Water Closets in Type B<br>Units - Increased Clearance<br>Depth - Forward Approach |
| Figure 1104.11.3.1.2(D)  | Clearance at Water Closets in Type B<br>Units - Clearance with Lavatory<br>Overlap              |
| Figure 1104.11.3.1.3.1   | Parallel Approach Bathtub in Type B Units-Option A Bathroom                                     |
| Figure 1104.11.3.1.3.2   | Forward Approach Bathtub in<br>Type B Units-Option A<br>Bathroom                                |
| Figure 1104.11.3.1.3.3(A | Transfer-type Shower Compartment in Type B Units  |
| Figure 1104.11.3.1.3.3(B | Transfer-type Shower Compartment in Type B Units - Exception                                    |
| Figure 1104.11.3.2.1     | Lavatory in Type B Units – Option B Bathroom  |
| Figure 1104.11.3.2.3.1   | Bathroom Clearance in Type B<br>Units – Option B Bathroom 157                                   |
| Figure 1104.12.1.1       | Minimum Clearance in Type B Units   |
| Figure 1104.12.1.2(A)    | U-shaped Kitchen Clearance in Type B Units158   |
| Figure 1104.12.1.2(B)    | U-shaped Kitchen Clearance in Type B Units - Exception  |
|                          |   |