

Flood Resistant Design and Construction

This document uses both the
International System of Units (SI)
and customary units

American Society of Civil Engineers

**Flood Resistant Design
and Construction**

This document uses both the International System of Units (SI) and customary units.



Library of Congress Cataloging-in-Publication Data

Flood resistant design and construction.

pages cm

“ASCE/SEI 24-14.”

ISBN 978-0-7844-1379-1 (print : alk. paper)—ISBN 978-0-7844-7872-1 (ebook)

1. Structural design—Standards. 2. Flood damage prevention—United States.
3. Building, Stormproof—United States. I. American Society of Civil Engineers.
TA658.2.F56 2015
624.1'76—dc23

2014035187

Published by American Society of Civil Engineers
1801 Alexander Bell Drive
Reston, Virginia, 20191-4382
www.asce.org/bookstore | ascelibrary.org

This standard was developed by a consensus standards development process that has been accredited by the American National Standards Institute (ANSI). Accreditation by ANSI, a voluntary accreditation body representing public and private sector standards development organizations in the United States and abroad, signifies that the standards development process used by ASCE has met the ANSI requirements for openness, balance, consensus, and due process.

While ASCE’s process is designed to promote standards that reflect a fair and reasoned consensus among all interested participants, while preserving the public health, safety, and welfare that is paramount to its mission, it has not made an independent assessment of and does not warrant the accuracy, completeness, suitability, or utility of any information, apparatus, product, or process discussed herein. ASCE does not intend, nor should anyone interpret, ASCE’s standards to replace the sound judgment of a competent professional, having knowledge and experience in the appropriate field(s) of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the contents of this standard.

ASCE has no authority to enforce compliance with its standards and does not undertake to certify products for compliance or to render any professional services to any person or entity.

ASCE disclaims any and all liability for any personal injury, property damage, financial loss, or other damages of any nature whatsoever, including without limitation any direct, indirect, special, exemplary, or consequential damages, resulting from any person’s use of, or reliance on, this standard. Any individual who relies on this standard assumes full responsibility for such use.

ASCE and American Society of Civil Engineers—Registered in U.S. Patent and Trademark Office.

Photocopies and permissions. Permission to photocopy or reproduce material from ASCE publications can be requested by sending an e-mail to permissions@asce.org or by locating a title in ASCE’s Civil Engineering Database (<http://cedb.asce.org>) or ASCE Library (<http://ascelibrary.org>) and using the “Permissions” link.

Errata: Errata, if any, can be found at <http://dx.doi.org/10.1061/9780784413791>.

Copyright © 2015 by the American Society of Civil Engineers.
All Rights Reserved.
ISBN 978-0-7844-1379-1 (print)
ISBN 978-0-7844-7872-1 (PDF)
Manufactured in the United States of America.

22 21 20 19 18 17 16 15

1 2 3 4 5

ASCE STANDARDS

In 2006, the Board of Direction approved the revision to the ASCE Rules for Standards Committees to govern the writing and maintenance of standards developed by the Society. All such standards are developed by a consensus standards process managed by the Society's Codes and Standards Committee (CSC). The consensus process includes balloting by a balanced standards committee made up of Society members and nonmembers, balloting by the membership of the Society as a whole, and balloting by the public. All standards are updated or reaffirmed by the same process at intervals not exceeding five years.

The material presented in this Standard has been prepared in accordance with recognized engineering principles. This

Standard should not be used without first securing competent advice with respect to its suitability for any given application. The publication of the material contained herein is not intended as a representation or warranty on the part of the American Society of Civil Engineers, or of any other person named herein, that this information is suitable for any general or particular use or promises freedom from infringement of any patent or patents. Anyone making use of this information assumes all liability from such use.

A complete list of currently available standards is available in the ASCE Library (<http://ascelibrary.org/page/books/s-standards>).

PREFACE

The material presented in this standard has been prepared in accordance with recognized engineering principles. This standard should not be used without first securing competent advice with respect to its suitability for any given application. The publication of the material contained herein is not intended as a representation or warranty on the part of the American Society of Civil Engineers, or of any other person named herein, that this information is suitable for any general or particular use or promises freedom from infringement of any patent or patents. Anyone making use of this information assumes all liability from such use.

The 2014 edition has a number of significant technical revisions from the 2005 edition, including

1. Defines Flood Design Class rather than using Risk/Occupancy Classification assigned under ASCE 7 and requires each building or structure governed by the standard to be assigned to Flood Design Class 1, 2, 3, or 4. Uses the assigned Flood Design Class to apply elevation requirements specified in Chapters 2, 4, 5, 6, and 7. Flood Design Class 4 buildings and facilities are equivalent to Occupancy Category/Risk Category IV buildings, which ASCE 7 identifies as essential facilities.
2. Adds definitions for Mixed Use and Residential Portions of Mixed Use in commentary to clarify limitations on use of dry floodproofing measures.
3. Changes the Coastal A Zone determination requirement from the designer's responsibility to one depending on either: (1) delineation of a Limit of Moderate Wave Action (LiMWA) on a Flood Insurance Rate Map, or (2) designation by the Authority Having Jurisdiction.
4. Separates specifications for flood openings from the installation requirements. Requires the presence of louvers, blades, screens, faceplates, or other covers and devices to be accounted for in determining net open area for non-engineered openings and in determining the performance of engineered openings. Revises coefficient of discharge table for engineered flood openings. Adds commentary regarding selection of coefficient of discharge and for grouping or stacking of flood openings.
5. For Flood Design Class 4 buildings, requires the minimum lowest floor elevation (or floodproofing level of protection) to be the higher of the Base Flood Elevation plus freeboard specified in Chapters 2, 4, and 6, the Design Flood Elevation, or the 500-year flood elevation. The 500-year flood elevation requirement is new.
6. Clarifies text pertaining to alluvial fan high risk flood hazard areas.
7. In Coastal High Hazard Areas (V Zone) and Coastal A Zones (if delineated),
 - a. Makes explicit that designs must account for local scour and erosion
 - b. Provides for shallow foundations in Coastal A Zones under certain circumstances
 - c. Requires flood openings in breakaway walls
 - d. Eliminates orientation of the lowest horizontal structural member as a factor to determine elevation for lowest floors, equipment, and flood damage-resistant materials
 - e. Requires exterior doors at the top of stairways that are located inside enclosed areas with breakaway walls
 - f. Consolidates requirements for all nonstructural concrete slabs
 - g. Allows substantial improvement of existing buildings seaward of the reach of mean high tide in V zones (makes ASCE 24 consistent with National Flood Insurance Program and Coastal A Zones).
8. Updates flood damage-resistant material requirements.
9. Clarifies emergency escape and rescue opening requirements for dry floodproofed buildings.
10. Clarifies requirements for garages, carports, and accessory storage structures. Adds new section for multistory parking structures.
11. Consolidates requirements for tanks and more clearly distinguishes between requirements based on flood hazard area.

ACKNOWLEDGMENTS

The American Society of Civil Engineers (ASCE) acknowledges the work of the Flood Resistant Design and Construction Standard Committee of the Codes and Standards Activities Division of the Structural Engineering Institute. This group comprises individuals from many backgrounds including consulting engineering, research, construction, education, government, design, and private practice.

This standard was prepared through the consensus standards process by balloting in compliance with procedures of ASCE's Codes and Standards Activities Committee. Those individuals who served on the ASCE 24-14 Standard Committee include

Christopher P. Jones, P.E., M.ASCE, Chair
Larry Buss, P.E., D.WRE, M.ASCE, CFM
Russell J. Coco, P.E., M.ASCE
James P. Colgate, RA, Esq., CFM
William L. Coulbourne, P.E., M.ASCE, F.SEI
James B. Destefano, P.E., AIA, F.SEI
Gary J. Ehrlich, P.E., M.ASCE
Shou-Shan Fan, Ph.D.
Kenneth J. Filarski, FAIA, AICP, LEED-AP BD+C, CFM,
SAP+AEER, NCARB
Daryle L. Fontenot, P.E., CFM

Carol Friedland, Ph.D., P.E., CFM
Michael J. Graham, CFM
John L. Ingargiola, EI, CBO, CFM
Catherine M. Kaake, P.E., M.ASCE
Philip Line, P.E., M.ASCE
E. Michael McCarthy, P.E., M.ASCE
Joseph J. Messersmith, Jr., P.E., M.ASCE
Kimberly Paarlberg, P.A.
John Squerciati, P.E., CFM, M.ASCE
Terri L. Turner, AICP, CFM
Robert A. Wessel, Ph.D., FASTM
Thomas G. Williamson, P.E., F.ASCE, F.SEI
Garland Wilson, P.E., M.ASCE

ASCE would like to thank each member of the committee for his or her dedication and hard work during completion of ASCE 24-14.

ASCE would like to acknowledge the long-standing contributions of previous Committee Chair, Harry B. Thomas, and of those current members who have served the committee since the development of the 1998 edition: William L. Coulbourne, Shou-Shan Fan, Christopher P. Jones, Joseph J. Messersmith, Jr., and Kimberly Paarlberg.

UNIT CONVERSIONS

Measurement	S.I. Units	Customary Units
Abbreviations	m = meter (S.I. base unit of length) cm = centimeter km = kilometer ha = hectare L = liter (S.I. base unit of volume) mL = milliliter kg = kilogram (S.I. base unit of mass) g = gram N = Newton (m·kg·s ⁻²) Pa = Pascal (N/m ²) kPa = kilopascal J = Joule W = watt kW = kilowatt s = second (S.I. base unit of time) min = minute h = hour day °C = degrees Celsius ppm = parts per million	yd = yard in. = inch mi = mile acre gal = gallon qt = quart lb = pound oz = ounce lbf = pound-force (lb/ft) psi = pounds per square inch atm = atmosphere ft·lbf = feet per pound-force Btu = British thermal unit hp = horsepower s = second min = minute h = hour day °F = degrees Fahrenheit ppm = parts per million
Length	1 m = 3.2808 ft = 1.0936 yd 1 cm = 0.3937 in. 1 km = 0.6214 mile	1 ft = 0.333 yd = 0.3048 m 1 in. = 2.54 cm 1 mile = 0.869 nautical mile = 1.6093 km
Area	1 m ² = 10.7643 ft ² 1 km ² = 0.3861 mi ² 1 ha = 2.4710 acre	1 ft ² = 0.0929 m ² 1 mi ² = 2.59 km ² 1 acre = 43,560 ft ² = 0.4047 ha
Volume	1 L = 0.2642 gal 1 ml = 1 cm ³	1 gal = 4 qt = 3.7854 L 1 ft ³ = 7.481 gal = 28.32 L
Mass	1 g = 0.0353 oz 1 kg = 2.2046 lb	1 oz = 28.3495 g 1 lb = 0.4536 kg
Force	1 N = 0.2248 lb/ft	1 lbf = 4.4482 N
Density	1 kg/m ³ = 0.2048 lb/ft ³ 1 kg/m ³ = 6.2427 lb/ft ³	1 lb/ft ³ = 4.882 kg/m ³ 1 lb/ft ³ = 16.018 kg/m ³
Pressure	1 kPa = 0.145 psi	1 psi = 6.8948 kPa 1 atm = 14.7 psi = 101.35 kPa
Energy and Power	1 J = 1.00 W·s = 0.7376 ft·lbf 1 kJ = 0.2778 W·h = 0.948 Btu 1 W = 0.7376 ft·lbf/s = 3.4122 Btu/h 1 kW = 1,3410 hp	1 ft·lbf = 1.3558 J 1 Btu = 1.0551 kJ 1 ft·lbf/s = 1.3558 W 1 hp = 550 ft·lb/s = 0.7457 kW
Flow	1 L/s = 15.85 gal/min = 2.119 ft ³ /min	1 gal/min = 0.1337 ft ³ /min = 0.0631 L/s
Concentration	mg/L = ppm _m (in dilute solutions)	
Temperature	°C = (°F - 32) × 5/9	°F = (°C × 9/5) + 32
Fundamental Constants and Relationships	Acceleration of gravity Density of freshwater (at 4 °C) = Density of saltwater (at 15 °C, 35 ppt) = Specific weight of freshwater (15 °C) = Specific weight of saltwater Weight of freshwater Weight of saltwater	32.2 ft/s ² = 9.81 m/s ² 1,000 kg/m ³ = 1 g/cm ³ 1,025 kg/m ³ = 1.025 g/cm ³ 62.4 lb/ft ³ = 9,810 N/m ³ 64.0 lb/ft ³ = 10,062 N/m ³ 1 gal = 8.345 lb = 3.7854 kg 1 gal = 8.559 lb = 3.8825 kg

CONTENTS

ASCE STANDARDS	iii
PREFACE	v
ACKNOWLEDGMENTS	vii
UNIT CONVERSIONS	ix
1.0 GENERAL	1
1.1 Scope	1
1.2 Definitions	1
1.3 Identification of flood hazard areas	5
1.4 Identification of flood-prone structures	5
1.4.1 General	5
1.4.2 Consideration for flood protective works	5
1.4.3 Assignment of Flood Design Class to buildings and structures.	6
1.4.3.1 Multiple flood design classes	6
1.5 Basic design and construction requirements.	6
1.5.1 General	6
1.5.2 Elevation requirements.	6
1.5.3 Foundation requirements.	6
1.5.3.1 Geotechnical considerations	6
1.5.3.2 Foundation depth.	6
1.5.3.3 Foundation walls and wall footings	6
1.5.3.4 Piers, posts, columns, or piles	6
1.5.4 Use of fill.	6
1.5.5 Anchorage and connections	6
1.6 Loads in flood hazard areas	7
1.6.1 General	7
1.6.2 Combination of loads	7
2.0 BASIC REQUIREMENTS FOR FLOOD HAZARD AREAS THAT ARE NOT IDENTIFIED AS COASTAL HIGH HAZARD AREAS AND COASTAL A ZONES	9
2.1 Scope	9
2.2 Development in floodways.	9
2.3 Elevation requirements.	9
2.4 Use of fill.	9
2.4.1 Structural fill	9
2.5 Slabs-on-grade and footings	9
2.5.1 Use of slabs-on-grade	9
2.5.2 Footing design	9
2.6 Foundation walls	9
2.7 Enclosures below the design flood elevation	10
2.7.1 Required openings in foundation walls and walls of enclosures	10
2.7.1.1 Openings in breakaway walls	10
2.7.2 Design of openings	10
2.7.2.1 Non-engineered openings	10
2.7.2.2 Engineered openings	10
2.7.3 Installation of openings	10
3.0 HIGH RISK FLOOD HAZARD AREAS	11
3.1 Scope	11
3.2 Alluvial fan areas.	11
3.2.1 Protective works in active alluvial fan areas	11
3.3 Flash flood areas	11
3.3.1 Protective works in flash flood areas	11

3.4	Mudslide areas	11
3.4.1	Protective works in mudslide areas	11
3.5	Erosion-prone areas	11
3.5.1	Protective works in erosion-prone areas	12
3.6	High velocity flow areas	12
3.6.1	Protective works in high velocity flow areas	12
3.7	Areas subject to wave action.	12
3.7.1	Coastal High Hazard Areas and Coastal A Zones.	12
3.7.2	Other high velocity wave action areas	12
3.8	Ice jam and debris areas	12
3.8.1	Protective works in ice jam and debris areas	12
4.0	COASTAL HIGH HAZARD AREAS AND COASTAL A ZONES	13
4.1	Scope	13
4.1.1	Identification of Coastal High Hazard Areas and Coastal A Zones.	13
4.2	General	13
4.3	Siting	13
4.4	Elevation requirements.	13
4.5	Foundation requirements.	13
4.5.1	General.	13
4.5.1.1	Shallow foundations in Coastal High Hazard Areas	13
4.5.1.2	Shallow foundations in Coastal A Zones	14
4.5.2	Special geotechnical considerations.	14
4.5.3	Foundation depth	14
4.5.4	Use of fill	14
4.5.5	Deep foundations	14
4.5.5.1	Attachments to piles	14
4.5.5.2	Piles terminating in pile caps or grade beams that are at or below grade	14
4.5.5.3	Piles extending to superstructure (structure framing).	14
4.5.5.4	Wood piles	14
4.5.5.5	Steel H piles	14
4.5.5.6	Concrete-filled steel pipe piles and shells	15
4.5.5.7	Prestressed concrete piles and precast concrete piles	15
4.5.5.8	Cast-in-place concrete piles	15
4.5.6	Pile design	15
4.5.6.1	Pile capacity	15
4.5.6.2	Capacity of the supporting soils	15
4.5.6.3	Minimum penetration	15
4.5.6.4	Foundation pile spacing	15
4.5.6.5	Wood pile connections.	15
4.5.6.6	Steel pile connections	15
4.5.6.7	Concrete pile connections	15
4.5.6.8	Pile splicing	15
4.5.6.9	Mixed types of piling and multiple types of installation methodology.	15
4.5.7	Posts, piers, and columns	16
4.5.7.1	Wood posts	16
4.5.7.2	Reinforced masonry columns	16
4.5.7.3	Reinforced concrete columns	16
4.5.8	Footings, mats, rafts, and concrete slabs that support columns or walls	16
4.5.9	Pile caps	16
4.5.10	Grade beams	16
4.5.11	Bracing.	16
4.5.12	Shear walls.	16
4.5.13	Stem walls	16
4.6	Enclosed areas below design flood elevation	17
4.6.1	Breakaway walls.	17
4.6.2	Openings in breakaway walls	17
4.7	Erosion control structures	17
5.0	MATERIALS	19
5.1	General	19
5.2	Specific materials requirements for flood hazard areas	19
5.2.1	Metal connectors and fasteners	19

5.2.2	Structural steel	19
5.2.2.1	Corrosive environments	19
5.2.2.2	Noncorrosive environments	19
5.2.3	Concrete	19
5.2.4	Masonry	20
5.2.5	Wood	20
5.2.5.1	Preservative treatment	20
5.2.5.2	Members and connections	20
5.2.6	Finishes	20
6.0	DRY FLOODPROOFING AND WET FLOODPROOFING.	21
6.1	Scope	21
6.2	Dry floodproofing	21
6.2.1	Dry floodproofing limitations	21
6.2.2	Dry floodproofing requirements	21
6.2.3	Limits on human intervention	21
6.3	Wet floodproofing	22
6.3.1	Wet floodproofing limitations on use	22
6.3.2	Wet floodproofing requirements	22
7.0	ATTENDANT UTILITIES AND EQUIPMENT	23
7.1	General	23
7.2	Electrical service	23
7.2.1	Service conduits and cables	23
7.2.2	Exposed conduits and cables	23
7.2.3	Electric meters	23
7.2.4	Panelboards, disconnect switches, and circuit breakers.	23
7.2.5	Electric elements installed below minimum elevations.	23
7.3	Plumbing systems	24
7.3.1	Buried plumbing systems	24
7.3.2	Exposed plumbing systems	24
7.3.3	Plumbing systems installed below minimum elevations	24
7.3.4	Sanitary systems	24
7.4	Mechanical, heating, ventilation, and air conditioning systems.	24
7.5	Elevators	24
7.5.1	Elevator shafts	24
8.0	BUILDING ACCESS	25
8.1	General	25
9.0	MISCELLANEOUS CONSTRUCTION	27
9.1	General	27
9.2	Decks and porches	27
9.2.1	Attached decks and porches	27
9.2.2	Detached decks and porches.	27
9.3	Concrete slabs	27
9.4	Garages, carports, and accessory storage structures.	27
9.4.1	Attached garages, carports, and accessory storage structures.	28
9.4.2	Detached garages, carports, and accessory storage structures	28
9.4.3	Multistory parking structures	28
9.5	Chimneys and fireplaces	28
9.6	Pools	28
9.6.1	Pools in flood hazard areas other than Coastal High Hazard Areas and Coastal A Zones	28
9.6.2	Pools in Coastal High Hazard Areas, Coastal A Zones, and other high risk flood hazard areas.	28
9.7	Tanks	29
9.7.1	Aboveground tanks	29
9.7.2	Underground tanks	29
10.0	REFERENCES	31

Commentary

C1	GENERAL	33
C1.1	Scope	33
C1.2	Definitions	34
C1.3	Identification of flood hazard areas	36
C1.4	Identification of flood-prone structures	38
C1.4.1	General	38
C1.4.2	Consideration for flood protective works	39
C1.4.3	Assignment of Flood Design Class to buildings and structures	39
C1.5	Basic design and construction requirements	40
C1.5.1	General	40
C1.5.2	Elevation requirements	40
C1.5.3	Foundation requirements	40
C1.5.3.1	Geotechnical considerations	40
C1.5.3.2	Foundation depth	40
C1.5.3.3	Foundation walls and wall footings	40
C1.5.3.4	Piers, posts, columns, or piles	41
C1.5.4	Use of fill	41
C1.5.5	Anchorage and connections	41
C1.6	Loads in flood hazard areas	41
C1.6.1	General	41
C1.6.2	Combination of loads	41
C2	BASIC REQUIREMENTS FOR FLOOD HAZARD AREAS THAT ARE NOT IDENTIFIED AS COASTAL HIGH HAZARD AREAS AND COASTAL A ZONES	43
C2.1	Scope	43
C2.2	Development in floodways	43
C2.3	Elevation requirements	43
C2.4	Use of fill	44
C2.4.1	Structural fill	44
C2.5	Slabs-on-grade and footings	44
C2.5.1	Use of slabs-on-grade	44
C2.7	Enclosures below the design flood elevation	44
C2.7.1	Required openings in foundation walls and walls of enclosures	45
C2.7.1.1	Openings in breakaway walls	45
C2.7.2	Design of openings	45
C2.7.2.1	Non-engineered openings	45
C2.7.2.2	Engineered openings	45
C2.7.3	Installation of openings	46
C3	HIGH RISK FLOOD HAZARD AREAS	47
C3.1	Scope	47
C3.2	Alluvial fan areas	47
C3.2.1	Protective works in active alluvial fan areas	48
C3.3	Flash flood areas	48
C3.3.1	Protective works in flash flood areas	48
C3.4	Mudslide areas	48
C3.5	Erosion-prone areas	49
C3.6	High velocity flow areas	49
C3.8	Ice jam and debris areas	49
C4	COASTAL HIGH HAZARD AREAS AND COASTAL A ZONES	51
C4.1	Scope	51
C4.1.1	Identification of Coastal High Hazard Areas and Coastal A Zones	51
C4.2	General	52
C4.3	Siting	53
C4.4	Elevation requirements	53
C4.5	Foundation requirements	53
C4.5.1	General	53
C4.5.1.1	Shallow foundations in Coastal High Hazard Areas	54
C4.5.1.2	Shallow foundations in Coastal A Zones	54

C4.5.3	Foundation depth	54
C4.5.4	Use of fill	54
C4.5.5	Deep foundations	54
C4.5.5.4	Wood piles	54
C4.5.5.6	Concrete-filled steel pipe piles and shells	55
C4.5.5.8	Cast-in-place concrete piles	55
C4.5.6	Pile design	55
C4.5.6.1	Pile capacity	55
C4.5.6.2	Capacity of the supporting soils	55
C4.5.6.3	Minimum penetration	55
C4.5.6.4	Foundation pile splicing	55
C4.5.7	Posts, piers, and columns	55
C4.5.7.3	Reinforced concrete columns	55
C4.5.8	Footings, mats, rafts, and concrete slabs that support columns or walls	56
C4.5.10	Grade beams	56
C4.5.11	Bracing	56
C4.5.12	Shear walls	56
C4.5.13	Stem walls	56
C4.6	Enclosed areas below design flood elevation	56
C4.6.1	Breakaway walls	56
C4.6.2	Openings in breakaway walls	56
C4.7	Erosion control structures	57
C5	MATERIALS	59
C5.1	General	59
C5.2.1	Metal connectors and fasteners	59
C5.2.2	Structural steel	59
C5.2.3	Concrete	59
C5.2.4	Masonry	60
C5.2.5	Wood	60
C6	DRY FLOODPROOFING AND WET FLOODPROOFING.	61
C6.1	Scope	61
C6.2	Dry floodproofing	61
C6.2.1	Dry floodproofing limitations	62
C6.2.2	Dry floodproofing requirements	62
C6.2.3	Limits on human intervention	62
C6.3	Wet floodproofing	62
C7	ATTENDANT UTILITIES AND EQUIPMENT	65
C7.1	General	65
C7.2	Electrical service	65
C7.2.5	Electric elements installed below minimum elevations	66
C7.3.3	Plumbing systems installed below minimum elevations	66
C7.3.4	Sanitary systems	66
C7.4	Mechanical, heating, ventilation, and air conditioning systems.	66
C7.5	Elevators	66
C7.5.1	Elevator shafts	66
C8	BUILDING ACCESS	67
C8.1	General	67
C9	MISCELLANEOUS CONSTRUCTION	69
C9.2	Decks and porches	69
C9.2.1	Attached decks and porches	69
C9.2.2	Detached decks and porches.	69
C9.3	Concrete slabs	69
C9.4	Garages, carports, and accessory storage structures.	69
C9.4.1	Attached garages, carports, and accessory storage structures.	69

C9.5	Chimneys and fireplaces	70
C9.6	Pools	70
C9.7	Tanks	70
C10	REFERENCES	71
	INDEX	73